

EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED), issued as "Forskrift om Skipsutstyr" by the Norwegian Maritime Authority. This Certificate is issued by DNV GL AS under the authority of the Government of Norway.

This is to certify:

That the Release mechanism for lifeboats and rescue boats (launched by a fall or falls)

with type designation(s)
HCHT 3,5

Issued to

H. Henriksen AS
TØNSBERG, Norway

is found to comply with the requirements in the following Regulations/Standards:

Regulation **(EU) 2018/773,**

item No. MED/1.26a. SOLAS 74 as amended, Reg. III/4, III/16, III/34 & X/3, LSA Code and 2000 HSC Code 8


Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until **2024-01-14.**

Issued at **Høvik** on **2019-01-15**

DNV GL local station:
Sandefjord

Approval Engineer:
Mats Asvold Innstø



Notified Body
No.: **0575**

for **DNV GL AS**

Roald Vårheim
Head of Notified Body



The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-surveillance module (D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU.

This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV GL AS of any changes to the approved equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled.

Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.



Job Id: **344.1-004186-2**
Certificate No: **MEDB00004R5**

Product description

Off-load Release Hook with Safe Working Load, SWL = 3500 kg

Application/Limitation

- Grades of materials as stated on drawings are to be delivered with maker's product certificates (3.1).
- The various components transferring the load like wires, shackles, hooks, etc. are to comply with international standard or code and are to be delivered with manufacturer's certificate, confirming a safety factor minimum 6 compared to the sustained load.
- Falls to be used with the launching appliance shall be of rotation-resistant and corrosion-resistant steel wire rope.
- Support to hull structure is not included in this examination and shall be evaluated separately.

Type Examination documentation

<u>Drawing No.</u>	<u>Rev.</u>	<u>Title</u>
HH006911	E16	HCHT 3,5
HH047228	-1	Hovedbolt
HH016909	A	Krokemne
HH026885	B6	Sideplate
HH026886	B5	Sideplate
M000142	A1	User Manual - HCH(T) CRANE HOOKS

Tests carried out

Prototype tested in accordance with IMO Resolution MSC.81(70) Part 1.

<u>Description</u>	<u>Report:</u>	<u>Date(s):</u>	<u>Witnessed by:</u>
Prototype test	18GNG49-2	2013-09-25	DNV GL Sandefjord, Norway

Marking of product

Marking shall be implemented in accordance with the LSA Code, item 1.2.2.9 and the Directive:

- Type designation, manufacturer name and serial number
- Safe Working Load, SWL

END OF CERTIFICATE